

Technical data	A-17	A-22	A-28
Power supply voltage		220/240V 50Hz 220/230V 60Hz	
Rated power		2300 W	
External dimensions W x H x D		480 x 500 x 600 mm	
Chamber dimensions Diam. x Depth	250 x 350 mm	250 x 450 mm	280 x 450 mm
Total weight	50 kg	51 kg	52 kg
Tank capacity		4.5 litres	
Autonomy (with max. water level)	From 7 to 11 cycles	From 6 to 10 cycles	From 5 to 9 cycles

CYCLE	Cycle type	Sterilization time (min.)	Cycle times including sterilization times, net of drying times (min.)			Drying*
			A-17	A-22	A-28	
134 °C UNIVERSAL	B	4	29	31	39	13-17
121 °C UNIVERSAL	B	20	45	48	52	13-17
134 °C VELOCE	S	4	21	24	27	1
134 °C WRAPPED SOLID INSTRUMENTS	S	4	20	24	28	13-17
134 °C PRION	B	18	43	45	53	13-17
xxx °C CUSTOM	S	Cycle can be personalised by user at temperatures 134 °C / 121 °C, process times starting from 4' (134 °C) or 20' (121 °C) with adjustable drying				
VACUUM TEST		TEST	18	18	19	
HELIX/B&D TEST VACUUM		TEST	20	24	28	
+ HELIX / B&D TEST (executed in sequence)		TEST	42	46	51	

*Drying varies according to machine model and volume
 Note: times do not take the max. pre-heating time into account (10 min.).
 Note: times may vary depending on the load and power supply.
 Note: 120 V model times may undergo increments up to a max. of 20%.

Due to our policy of constant technological upgrading, the technical specifications may be subject to change without prior notice. According to the regulations in force, some products and/or features may have different availability and characteristics in areas outside of the European Union. Please contact your local distributor.



Making Your Life Better.

BU Medical Equipment

**Sede legale ed amministrativa
Headquarters**

Cefla s.c.
 Via Selice Provinciale, 23/a
 40026 Imola - Bo (Italy)
 tel. +39 0542 653111
 fax +39 0542 653344

**Stabilimento
Plant**

Via Bicocca, 14/c
 40026 Imola - Bo (Italy)
 tel. +39 0542 653441
 fax +39 0542 653601



ANTHOS A AUTOCLAVES

- A-17
- A-22
- A-28



UNCOMPROMISING QUALITY



The best seller

**3 VOLUMES,
ONE SIZE**

The A range is available in the 17, 22, and 28-litre versions. Three different capacities to allow users to choose the most suitable machine according to their needs. External

dimensions, being the same for the three machines, make installation easier. The 17 and 22 litre models have five trays while the 28-litre model has six.



LCD DISPLAY



Water management.

The doors on the upper part of the steriliser allow the operator to reach the tanks to fill them with demineralised water and clean them. The in-tank sensor checks water quality and ensures long-lasting machine performance.



Remote technical support with Easy Check.

All sterilisers of the A range are equipped with incorporated Wi-Fi and Ethernet port. Connected to the Internet by enabling the Easy Check service, they can receive remote support. Intervention times can be significantly reduced thereby allowing technicians to keep machines constantly efficient.



Traceability software.

MyTrace is the traceability software available for A. By using this programme, each set of sterilised instruments can be associated to the patient through a bar code. This essential software completes the sterilisation process and provides legal protection to dentists.



USB.

The cycle reports are saved automatically inside the steriliser's memory. Later on, they can be downloaded through the front USB port. The PDF files can be viewed on any device.



Printer.

The A range can be completed with an external printer available as an optional accessory, able to provide reports or bar code labels.

Provided with keypad, it features clear user-friendly icons. The operator's task is made easier and faster thanks to on-display availability of all data. Easy to install, a simple guided procedure aids the initial configuration.